








EILUX UNIVERSAL DC ADAPTOR STANDARD


Date: Jan., 2012 / EILUX

SAFETY STD	INPUT VOLTAGE	OUTPUT	JACK SIZE	CABLE LENGTH	FIT FOR EILUX MODEL	PLUG IMAGE
AS / NZS Australia & New Zealand	100-240V 50/60 Hz	DC 9V 400mA	3.5mm / L Shape	185cm	For 1 ~ 5-watch winder models	
	240V 50Hz	DC 9V 1 A	5.5mm / L Shape	180cm	For 6 ~ 24-watch winder models	
BS United Kingdom countries	100-240V 50/60 Hz	DC 9V 400mA	3.5mm / L Shape	185cm	For 1 ~ 5-watch winder models	
	230V 50Hz	DC 9V 1 A	5.5mm / L Shape	180cm	For 6 ~ 24-watch winder models	
CCC China	100-240V 50/60 Hz	DC 9V 400mA	3.5mm / L Shape	185cm	For 1 ~ 5-watch winder models	
	230V 50Hz	DC 9V 1 A	5.5mm / L Shape	180cm	For 6 ~ 24-watch winder models	
GS / CE / TUV European Union	100-240V 50/60 Hz	DC 9V 400mA	3.5mm / L Shape	185cm	For 1 ~ 5-watch winder models	
	240V 50Hz	DC 9V 1 A	5.5mm / L Shape	180cm	For 6 ~ 24-watch winder models	
PSE / JET Japan	100-240V 50/60 Hz	DC 9V 400mA	Ø3.5mm / L Shape	185cm	For 1 ~ 5-watch winder models	
	100V 60Hz	DC 9V 1 A	Ø5.5mm / L Shape	180cm	For 6 ~ 24-watch winder models	
U/L North America & Canada	100-240V 50/60 Hz	DC 9V 400mA	Ø3.5mm / L Shape	185cm	For 1 ~ 5-watch winder models	
	120V 60Hz	DC 9V 1 A	Ø5.5mm / L Shape	180cm	For 6 ~ 24-watch winder models	

"L" sharp with Ø3.5mm



"L" sharp with Ø5.5mm



DC ADAPTOR MAIN BODY



Safety Approval:

Adaptor provided is approved by one or more of the following safety standard.

